

ABBRIATA®




Rotopressa
Round baler
M100 Super
M100 Magnum





Vista laterale macchina ballone a centro morbido formato in camera fissa a catena e traversine.
Lateral view with a sketch of soft center round bale made by fixed chamber with chain and bars.



Raccoglitore di larghezza massima 145 cm.
Pick-up max width 145 cm.



Vista posteriore con allontanatore, rullo, denti infaldatore e catenaria con traversine.
Rear view with bale chute, roll, packer device teeth and chain & bars.

Rotopressa M100 SUPER - M100 MAGNUM

DATI TECNICI		M100 SUPER	M100 MAGNUM
Dimensioni balla	cm	Ø 100 x 100	Ø 100 x 100
	inches	Ø 39,3 x 39,3	Ø 39,3 x 39,3
Larghezza del raccoglitore	cm	145	165 (con coclee laterali)
	inches	57	64,9
Traversine	n°	27	27
P.D.F. giri/min.		540	540
Potenza richiesta	CV	40/45	40/45
Dimensioni: (La x Lu x H)	cm	180 [195] x 302 x 177	225 x 302 x 177
	inches	70,8 [76,7] x 118,8 x 69,7	88,5 x 118,8 x 69,7
Peso	Kg	1.590	1.650
	lb	3.490	3.636
Pneumatici		7.50-16 [or 11.5-80/15]	11.5-80/15

EQUIPAGGIAMENTI DI SERIE

Apertura portellone a comando idraulico e chiusura meccanica - Apertura rapida portellone senza disinserire la P.d.F. - Sollevamento idraulico del raccoglitore - Infaldatore - Carreggiata variabile - Timone regolabile - Contaballe - Impianto illuminazione - Albero cardanico con limitatore - Ruotino retrattile del raccoglitore - Doppio bilanciamento del raccoglitore - Legatore automatico monofilo a comando elettrico - Allontanatore

EQUIPAGGIAMENTI OPZIONALI

Legatura a rete a comando elettrico (non fornibile in abbinamento a legatura a spago) - Legatura a doppio spago a comando elettrico - Avvisatore acustico/luminoso - Ruotino supplementare del raccoglitore - Doppio ruotino raccoglitore pneumatico a regolazione rapida (di serie per "M100 Magnum") - Ruote maggiorate - Albero cardanico grandangolo - Freno idraulico

Round baler M100 SUPER - M100 MAGNUM

TECHNICAL SPECIFICATIONS		M100 SUPER	M100 MAGNUM
Bale size	cm	Ø 100 x 100	Ø 100 x 100
	inches	Ø 39.3 x 39.3	Ø 39.3 x 39.3
Pick-up width	cm	145	165 (with augers)
	inches	57	64.9
Chain shafts	n°	27	27
P.T.O. rpm		540	540
Required power	CV	40/45	40/45
Dimensions (W x L x H)	cm	180 [195] x 302 x 177	225 x 302 x 177
	inches	70.8 [76.7] x 118.8 x 69.7	88.5 x 118.8 x 69.7
Weight	Kg	1,590	1,650
	lb	3,490	3,636
Tyres		7.50-16 [or 11.5-80/15]	11.5-80/15

STANDARD EQUIPMENT

Tail gate with hydraulic control and mechanic lock - Quick tail gate without P.T.O. disconnection - Hydraulic pick-up lift - Packer device - Changeable wheel-track - Adjustable drawbar - Bale counter - Lights - Cardan shaft with limiter - Small retractable pneumatic wheel for pick-up - Double pick-up balancing - Electrically driven automatic monowire binding device - Bale chute

SPECIAL EQUIPMENT

Electrically driven net binding device (not available in combination with a twine binding device) - Electrically driven double twine binding device - Signal horn + light - Additional pick-up wheel - Double pneumatic pick-up wheel with quick control (standard for "M100 Magnum") - Oversize wheels - Wide angle cardan shaft - Hydraulic brake

Le caratteristiche indicate sono a titolo informativo e non impegnativo e possono essere variate in qualsiasi momento, senza preavviso.

L'impianto di illuminazione è fornito di serie solo per l'Italia. A richiesta per altri paesi.

The above mentioned characteristics are only informative and not binding, they may be changed at any moment without notice.

The electrical plant is standard equipment only for Italy. At request for other countries.



casa fondata nel 1896

ABBRIATA® s.r.l.
Via F.lli Rosselli, 2
Tel. +39 0131 703117 r.a.
Fax +39 0131 703506
15079 SEZZADIO (AL) ITALIA
<http://www.abbriate.com>
e-mail: abbriate@abbriate.com

